

Fiche technique [https://tech-info.glasurit.com/fr\\_FR/CV\\_VOC/58-1250\\_M.pdf](https://tech-info.glasurit.com/fr_FR/CV_VOC/58-1250_M.pdf)

Fiche hygiène et sécurité

Finition à utiliser pour toutes applications où un brillant moyen est souhaité sur les châssis (changement de coloris) et les conteneurs.

Produit à utiliser sur tous les impressions-apprêts ou apprêts PL Glasurit et offrant un bel aspect, une haute efficacité, un fort pouvoir couvrant, une excellente dureté de la surface et une excellente résistance aux UV.



58-1250 M

## DISCLAIMER

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at <http://techinfo.glasurit.com> or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.