

# A-B-91

Styrene-free body filler, universal



A brand of BASF –  
We create chemistry

<b>Application:</b>	AraClass - undercoat solutions.
<b>Key Features:</b>	Styrene-free coarse and fine body filler - sustainable use. Fast drying, easy to sand and good adhesion.
<b>Remarks:</b>	Stir well before use. Mix intensively to avoid any marbleizing effect.

## Handling

### Product suitable on

- OEM parts with e-coat
- Old paintwork
- GRP / SMC
- Sheet steel
- Aluminium
- Galvanised sheet steel



**Mixing Ratio** 100 % by weight A-B-91



**Hardener** 2 % by weight G-H-110



**Spray viscosity at 20°C** DIN 4: **Potlife at 20°C** 4 min



**Drying at 20°C** 20 min

**Drying at 60°C** 5 min



**Infrared (short wave)** 5-6 min

## Safety advice:

The products are suitable for professional use only.

It cannot be ruled out that this product contains particles < 0.1 µm.

**2004/42/II(b)(250)249:** The EU limit value for this product (product category: IIB.b) in ready-for-use form is max 250 g/litre of VOC. The VOC content of this product is 249 g/l.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at [www.glasurit.com](http://www.glasurit.com) or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

# A-B-91

Styrene-free body filler, universal



A brand of BASF –  
We create chemistry



**Orbital sanding, dry**

P150 / P240 (use Guide Coat)

---

Please note: For automotive refinish, repair instructions of vehicle manufacturers, in particular regarding installed sensor technology, must always be observed in addition to the processing instructions given within this document.

---

#### **Safety advice:**

The products are suitable for professional use only.

It cannot be ruled out that this product contains particles < 0.1 µm.

**2004/42/IIIB(b)(250)249:** The EU limit value for this product (product category: IIB.b) in ready-for-use form is max 250 g/litre of VOC. The VOC content of this product is 249 g/l.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at [www.glasurit.com](http://www.glasurit.com) or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

BASF Coatings GmbH - Automotive Refinish Coatings Solutions Europe - Glasuritstrasse 1 - 48165 Münster - Germany

04/2022